

# SPECIFICATIONS FOR GTM PORTABLE LIGHT TOWER

<b>PORTABLE LIGHT TOWER S120-875W</b>	
<b>UL -CSA APPROVED</b>	
<b>POWER SOURCE</b>	120V A.C. ~60Hz
Current requirements	9A
<b>LAMP</b>	
Lamp	Metal halide
Power consumed	875W – 20,000 Hr .Ave. Life
Lumen	95000 lm
Colour temperature	4000 °K
Socket	E39
<b>ELECTRIC INFLATOR</b>	
Power source	120 V A.C. ~60HZ 500W
<b>STRUCTURE</b>	
Body	High-calibre flame-retardant fibreglass
Total dimensions (case)	24" (610 mm) long x 18" (460mm) wide x 24" (610 mm) high
Total dimensions (while functioning)	24" (610 mm) long X 18" (460mm) wide x 15.5' (4720mm) high
Weight	66 lb. (30 Kg)
Standard colours	Red, yellow, blue
Custom colours, by request	Additional fee
<b>FABRIC TUBE</b>	
Material	Resin-treated rip-stop nylon
Reinforcement at tube base	Vinyl
Tube length	13.8' (4200 mm)
Diameter	16" (400 mm)
Reflector hole diameter	8" (200 mm)
Personalized text or illustrations, by request	Additional fee
<b>ACCESSORIES</b>	
Anchor stakes	4
Tethers	4
<b>OPERATING ENVIRONMENT</b>	
Altitude	Max. 3280' (1000m)
Operating temperature	+5°F to +104°F (-15°C to +40°C)